

Backlit LED Traffic Controller BLB77R-270

PRODUCT NUMBER

1936

CABINET DIMENSIONS

7" H x 7" W x 3" D

ILLUMINATION SOURCE

Backlit with super-bright LEDs

Available in green, red, blue, amber, and white LEDs

Messages "blankout" when turned off, eliminating confusion

Long life, solid state lighting

ELECTRICAL

Standard Voltage: 120 VAC, Optional Voltages: 12 V, 24 V, 240 V, 277 VAC

Maximum amps per lighted message (at 120 V) shown in the table below

CONSTRUCTION

Faces: Single Faced Sign

Extrusion (BLB): 3" deep mitered corrosion resistant aluminum housing

Face Material (BLB): Dark tinted acrylic 1/8" thick.

Message Panel Material: Milk white acrylic 1/8" thick.

Vinyl Style: Vinyl is applied in a reverse stencil cut style

Vinyl Color: Applied vinyl color is black

FINISH

Standard Cabinet Color: Duranodic Bronze

Custom colors available upon request

MESSAGE	COLOR	HEIGHT	AMPS
X-RAY IN USE	50° Red Diffused	1.25"	0.07

Directional Systems

1419 West 26th St.

Erie, PA 16508

Phone: (877) 827-8296

Fax: (877) 827-8291

Email: sales@directionalsystems.com

Website: www.directionalsystems.com



Directional Systems

Proudly Made in the USA

Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.

