Outdoor Blank-out LED Direct-view Sign MODEL TCL718R-135DS/12-24VDC DIMENSIONS 7" H x 18" W x 2.5" D (est. 4.394 lbs) **CLASS** CLASS: TCL Series Control Method: Switch (not included) or external relay. CONSTRUCTION Back Construction: 0.050" Lift-n-Shift Back Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep. Face Material: 1/8" impact resistant, smoke-tinted acrylic (5109) Faces: Single Faced Sign Finish: Duranodic Bronze Mounting Channel: None **ELECTRICAL** Flashing: Not Included Input Voltage: 12-24 VDC $\bullet \bullet \bullet \bullet \bullet \bullet$ Photodimming: None UL/cUL Listed: Listed for wet locations $\bullet \bullet \bullet \bullet \bullet \bullet$ MESSAGE Illumination: Super bright direct view LEDs. Message blanks out when off. $\bullet \bullet \bullet \bullet \bullet \bullet$ $\bullet \bullet \bullet \bullet \bullet \bullet$ Sign Messages: See message table below $\bullet \bullet \bullet \bullet \bullet \bullet$ 2 5" 18" MESSAGE LED/COLOR |HEIGHT|AMPS FULL Red Wide Angle LED 4.375" 0.667-0.333 Frame Detail NOTE: Above messages are independently controlled. **Directional Systems** 2201 W 50th Št. **Directional** Systems Erie. PA 16509 Phone: (877) 827-8296 Fax: (877) 827-8291 Email: sales@directionalsystems.com Website: www.directionalsystems.com

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.

Product View

PRODUCT ID: 30139