## PRODUCT ID: 39525

Outdoor Blank-out LED Backlit Sign

#### MODEL

PHX734R-J310/120-277VAC



#### DIMENSIONS

7" H x 34" W x 2.5" D (est. 7.151 lbs)

#### **CLASS**

Class: PHX Series

Control Method: Switch (not included) or external relay.

#### CONSTRUCTION

Back Construction: 0.050" Lift-n-Shift Back

Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep.

Face Material: 1/8" thick, dark grey diffused acrylic

Faces: Single Faced Sign Finish: Duranodic Bronze

Graphic: Printed graphic applied to surface Mounting Channel: None

#### **ELECTRICAL**

Flashing: Not Included Input Voltage: 120-277 VAC
UL/cUL Listed: Listed for wet locations

### **MESSAGE**

Color: Black opaque Font: Swiss 721 Bold BT

Illumination: Backlit with high intensity LEDs. Message blanks out when off

Sign Messages: See message table below

#### LED/COLOR | HEIGHT | AMPS **MESSAGE** Clearance 8' 6" Red Wide Angle LED 3.25" 0.231-0.100

NOTE: Above messages are independently controlled.

#### **Directional Systems**

2201 W 50th St. Erie. PA 16509 Phone: (877) 827-8296

Fax: (877) 827-8291

**Directional** Systems

Email: sales@directionalsystems.com Website: www.directionalsystems.com

# **Product View**

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.





Frame Detail

