PRODUCT ID: 40214

Indoor LED Backlit Sign

MODEL

SBLF811W-A209R/120-277VAC



DIMENSIONS

8" H x 11" W x 2.5" D (est. 2.86 lbs)

CLASS

Class: SBLF Series

Control Method: Switch (not included) or external relay.

CONSTRUCTION

Back Construction: 0.050" Lift-n-Shift Back

Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep.

Face Material: 1/8" thick, impact modified acrylic (0000)

Faces: Single Faced Sign Finish: Duranodic Bronze

Graphic: Printed graphic applied to surface

ELECTRICAL

Flashing: Not Included Input Voltage: 120-277 VAC UL/cUL Listed: Listed

MESSAGE

Color: Red translucent Font: Swiss 721 Bold BT

Illumination: Backlit with white LEDs. Message always visible.

Sign Messages: See message table below

MESSAGE	LED/COLOR	HEIGHT	AMPS
ROOM IN USE	White Wide Angle I FD	2.0"	0.059-0.026

NOTE: Above messages are independently controlled.

Directional Systems


2201 W 50th St. Erie. PA 16509

Directional Systems Phone: (877) 827-8296 Fax: (877) 827-8291

Email: sales@directionalsystems.com Website: www.directionalsystems.com

Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



Frame Detail



11232022 | DP