PRODUCT ID: 14864

Outdoor Blank-out LED Direct-view Sign

MODEL TCL734GGR-C210/120-277VAC



DIMENSIONS 7" H x 34" W x 2.5" D (est. 7.55 lbs)

CLASS

CLASS: TCL Series Control Method: Switch (not included) or external relay.

CONSTRUCTION

Back Construction: 0.050" Lift-n-Shift Back Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep. Face Material: 1/8" impact resistant, smoke-tinted acrylic (5109) Faces: Single Faced Sign Finish: Duranodic Bronze Mounting Channel: None

ELECTRICAL


Flashing: Not Included Input Voltage: 120-277 VAC Photodimming: None UL/cUL Listed: Listed for wet locations

MESSAGE

Illumination: Super bright direct view LEDs. Message blanks out when off. Sign Messages: See message table below

MESSAGE	LED/COLOR	HEIGHT	AMPS
DRIVE UP	Green Wide Angle LEDs	2.5"	0.081-0.035
OPEN	Green Wide Angle LEDs	3.5"	0.055-0.024
CLOSED	Red Wide Angle LEDs	3.5"	0.041-0.018
	ee ere independently ee	atrollad	
NOTE. Above messag	les are independently co	ntrollea.	
Directional Systems 2201 W 50th St.			
Erie, PA 16509 Phone: (877) 827-8296	Direc	tior Svs	a tems
Fax: (877) 827-8291			

Website: www.directionalsystems.com



Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



Sample Display Options



03022023 | DP