PRODUCT ID: 20304

Outdoor Blank-out LED Direct-view Sign

MODEL

TCL1434G-125DS/120-277VAC



DIMENSIONS

14" H x 34" W x 2.5" D (est. 14.045 lbs)

CLASS

CLASS: TCL Series

Control Method: Switch (not included) or external relay.

CONSTRUCTION

Back Construction: 0.050" Lift-n-Shift Back

Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep.

Face Material: 1/8" impact resistant, smoke-tinted acrylic (5109)

Faces: Single Faced Sign Finish: Duranodic Bronze Mounting Channel: None

ELECTRICAL

Flashing: Not Included Input Voltage: 120-277 VAC Photodimming: None
UL/cUL Listed: Listed for wet locations

MESSAGE

Illumination: Super bright direct view LEDs. Message blanks out when off.

Sign Messages: See message table below

MESSAGE	LED	/COL	.OR	HEIGHT	AMPS
•	 			40 ="	A A / = A / A =

ATM Green Wide Angle LED | 10.5" | 0.247-0.107

NOTE: Above messages are independently controlled.

Directional Systems

2201 W 50th St. Erie. PA 16509 Phone: (877) 827-8296

Fax: (877) 827-8291



Email: sales@directionalsystems.com Website: www.directionalsystems.com **Product View**

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.





