# PRODUCT ID: 38657

Indoor Blank-out LED Backlit Sign

### MODEL

SBL1212R-193/120-277VAC



## **DIMENSIONS**

12" H x 12" W x 2.5" D (est. 3.446 lbs)

# **CLASS**

Class: SBL Series

Control Method: Switch (not included) or external relay.

# **CONSTRUCTION**

Back Construction: 0.050" Lift-n-Shift Back

Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep.

Face Material: 1/8" thick, dark grey diffused acrylic

**Faces**: Single Faced Sign **Finish**: Duranodic Bronze

Graphic: Printed graphic applied to surface

### **ELECTRICAL**

Flashing: Not Included Input Voltage: 120-277 VAC UL/cUL Listed: Listed

### **MESSAGE**

Color: Black opaque Font: Swiss 721 Bold BT

Illumination: Backlit with LEDs. Message blanks out when off.

Sign Messages: See message table below

MESSAGE	LED/COLOR	HEIGHT	<b>AMPS</b>
LASER IN USE	Red Wide Angle I FD	2.25"	0.065-0.028

NOTE: Above messages are independently controlled.

#### **Directional Systems**

2201 W 50th St. Erie, PA 16509 Phone: (877) 827-8296

**Directional**Systems

Fax: (877) 827-8291 Email: sales@directionalsystems.com Website: www.directionalsystems.com

# **Product View**

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



