

PRODUCT ID: 38676

Indoor Blank-out LED Backlit Sign

MODEL SBL77R-945/120-277VAC

DIMENSIONS 7" H x 7" W x 2.5" D (est. 2.625 lbs)

CLASS Class: SBL Series Control Method: Switch (not included) or external relay.

CONSTRUCTION

Back Construction: 0.050" Lift-n-Shift Back Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep. Face Material: 1/8" thick, dark grey diffused acrylic Faces: Single Faced Sign Finish: Duranodic Bronze Graphic: Printed graphic applied to surface

ELECTRICAL

Flashing: Not Included Input Voltage: 120-277 VAC UL/cUL Listed: Listed

MESSAGE

Color: Black opaque Font: Swiss 721 Bold BT Illumination: Backlit with LEDs. Message blanks out when off. Sign Messages: See message table below

> MESSAGE LED/COLOR | HEIGHT | AMPS CT IN USE Red Wide Angle LED 1.25" 0.026-0.011

NOTE: Above messages are independently controlled.

Directional Systems 2201 W 50th Št. Erie. PA 16509 Phone: (877) 827-8296 Fax: (877) 827-8291 Email: sales@directionalsystems.com Website: www.directionalsystems.com

Copyright (C) 2025 Directional Systems

09212023 | JTC