PRODUCT ID: 38690

Indoor Blank-out LED Backlit Sign

MODEL

SBL77R-C062/120-277VAC



DIMENSIONS

7" H x 7" W x 2.5" D (est. 1.935 lbs)

CLASS

Class: SBL Series

Control Method: Switch (not included) or external relay.

CONSTRUCTION

Back Construction: 0.050" Lift-n-Shift Back

Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep.

Face Material: 1/8" thick, dark grey diffused acrylic

Faces: Single Faced Sign Finish: Duranodic Bronze

Graphic: Printed graphic applied to surface

ELECTRICAL

Flashing: Not Included Input Voltage: 120-277 VAC UL/cUL Listed: Listed

MESSAGE

Color: Black opaque Font: Swiss 721 Bold BT

Illumination: Backlit with LEDs. Message blanks out when off.

Sign Messages: See message table below

MESSAGE	LED/COLOR	HEIGHT	AMPS
DOOR OPEN	Red Wide Angle LED	1.5"	0.026-0.011

NOTE: Above messages are independently controlled.

Directional Systems


2201 W 50th St. Erie. PA 16509 Phone: (877) 827-8296

Directional Systems Fax: (877) 827-8291

Email: sales@directionalsystems.com Website: www.directionalsystems.com

Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



Frame Detail

