## **Product View** PRODUCT ID: 38774 NOTE: Sign image may not exactly represent the finished product. For illustration purposes only. Indoor Blank-out LED Backlit Sign MODEL SBL811R-130/120-277VAC DIMENSIONS 8" H x 11" W x 2.5" D (est. 2.761 lbs) **CLASS** Class: SBL Series Control Method: Switch (not included) or external relay. CONSTRUCTION Back Construction: 0.050" Lift-n-Shift Back Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep. Face Material: 1/8" thick, dark grey diffused acrylic Faces: Single Faced Sign Finish: Duranodic Bronze Graphic: Printed graphic applied to surface **ELECTRICAL** Flashing: Not Included Input Voltage: 120-277 VAC UL/cUL Listed: Listed 8 in MESSAGE Color: Black opaque Font: Swiss 721 Bold Condensed BT Illumination: Backlit with LEDs. Message blanks out when off. Sign Messages: See message table below MESSAGE LED/COLOR | HEIGHT | AMPS DO NOT ENTER Red Wide Angle LED 2.5" 0.039-0.017 ⊲—2 1/2 in—⇒ -11 in Frame Detail NOTE: Above messages are independently controlled. **Directional Systems** 2201 W 50th Št. **Directional** Systems Erie. PA 16509 Phone: (877) 827-8296

Email: sales@directionalsystems.com Website: www.directionalsystems.com

Fax: (877) 827-8291