PRODUCT ID: 38786

Indoor Blank-out LED Backlit Sign

MODEL

SBL811R-A231/120-277VAC



DIMENSIONS

8" H x 11" W x 2.5" D (est. 5.277 lbs)

CLASS

Class: SBL Series

Control Method: Switch (not included) or external relay.

CONSTRUCTION

Back Construction: 0.050" Lift-n-Shift Back

Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep.

Face Material: 1/8" thick, dark grey diffused acrylic

Faces: Single Faced Sign **Finish**: Duranodic Bronze

Graphic: Printed graphic applied to surface

ELECTRICAL

Flashing: Not Included Input Voltage: 120-277 VAC UL/cUL Listed: Listed

MESSAGE

Color: Black opaque Font: Swiss 721 Bold BT

Illumination: Backlit with LEDs. Message blanks out when off.

Sign Messages: See message table below

| MESSAGE | LED/COLOR | HEIGHT | AMPS |
|---------|--------------------|--------|-------------|
| REAM ON | Red Wide Angle LED | 2 25" | 0.039-0.017 |

NOTE: Above messages are independently controlled.

Directional Systems


2201 W 50th St. Erie, PA 16509 Phone: (877) 827-8296



Fax: (877) 827-8291 Email: sales@directionalsystems.com Website: www.directionalsystems.com

Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



Frame Detail

