

## PRODUCT ID: 38982

### Outdoor Blank-out LED Backlit Sign

#### MODEL

PHX1434GGR-256



#### DIMENSIONS

14" H x 34" W x 2.25" D (est. 9.324 lbs)

#### CLASS

Class: PHX Series

Control Method: Switch (not included) or external relay.

#### CONSTRUCTION

Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.25" deep.

Face Material: 1/8" thick, dark grey diffused acrylic

Faces: Single Faced Sign

Finish: Duranodic Bronze

Mounting Channel:

#### ELECTRICAL

Flashing: Not Included

Input Voltage: 120-277 VAC

UL/cUL Listed: Listed for wet locations

#### MESSAGE

Color: Black opaque

Font: Swiss 721 Bold BT

Illumination: Backlit with high intensity LEDs. Message blanks out when off

Sign Messages: See message table below

MESSAGE	LED/COLOR	HEIGHT	AMPS
COMMERCIAL	Green Wide Angle LED	3.5"	0.827-0.358
OPEN	Green Wide Angle LED	3.5"	0.413-0.179
CLOSED	Red Wide Angle LED	3.5"	0.267-0.116

NOTE: Above messages are independently controlled.

#### Directional Systems

2250 West 23rd St

Erie, PA 16506

Phone: (877) 827-8296

Fax: (877) 827-8291

Email: sales@directionalsystems.com

Website: [www.directionalsystems.com](http://www.directionalsystems.com)

Proudly Made in the USA



## Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.

