### PRODUCT ID: 39004

Outdoor LED Backlit Sign

#### MODEL

PHXF734W-D376/120-277VAC



#### DIMENSIONS

7" H x 34" W x 2.25" D (est. 6.948 lbs)

#### **CLASS**

**CLASS**: PHXF Series

Control Method: Switch (not included) or external relay.

#### CONSTRUCTION

Back Construction: 0.050" Lift-n-Shift Back

Cabinet: 1-piece, corrosion resistant, extruded all-weather frame, 2.25" deep.

Face Material: 1/8" thick, impact modified acrylic (0000)

Faces: Single Faced Sign Finish: Duranodic Bronze

Graphic: Printed graphic applied to surface Mounting Channel: None

#### **ELECTRICAL**

Flashing: Not Included Input Voltage: 120-277 VAC
UL/cUL Listed: Listed for wet locations

#### **MESSAGE**

Color: Blue translucent Font: Swiss 721 Bold BT

Illumination: White high intensity LED backlit. Message always visible.

Sign Messages: See message table below

MESSAGE	LED/COLOR	HEIGHT	AMPS
EMPLOYEE PARKING	White Wide Angle LED	2.25"	0.347-0.150

NOTE: Above messages are independently controlled.

#### **Directional Systems**

2201 W 50th St. Erie. PA 16509 Phone: (877) 827-8296

Fax: (877) 827-8291


**Directional**Systems

Email: sales@directionalsystems.com Website: www.directionalsystems.com

## **Product View**

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.

# **EMPLOYEE PARKING**



Frame Detail

