

PRODUCT ID: 39006

Outdoor LED Backlit Sign

MODEL

PHXF718W-125G



DIMENSIONS

7" H x 18" W x 2.25" D (est. 3.79 lbs)

CLASS

CLASS: PHXF Series

Control Method: Switch (not included) or external relay.

CONSTRUCTION

Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.25" deep.

Face Material: 1/8" thick, white acrylic (7328)

Faces: Single Faced Sign

Finish: Duranodic Bronze

Mounting Channel:

ELECTRICAL

Flashing: Not Included

Input Voltage: 120-277 VAC

UL/cUL Listed: Listed for wet locations

MESSAGE

Color: Green translucent

Font: Swiss 721 Bold BT

Illumination: White high intensity LED backlit. Message always visible.

Sign Messages: See message table below

MESSAGE	LED/COLOR	HEIGHT	AMPS
---------	-----------	--------	------

ATM	White Wide Angle LED	5.0"	0.195-0.084
-----	----------------------	------	-------------

NOTE: Above messages are independently controlled.

Directional Systems

2250 West 23rd St

Erie, PA 16506

Phone: (877) 827-8296

Fax: (877) 827-8291

Email: sales@directionalsystems.com

Website: www.directionalsystems.com

Proudly Made in the USA



Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.

