Product View PRODUCT ID: 39349 NOTE: Sign image may not exactly represent the finished product. For illustration purposes only. Indoor Blank-out LED Backlit Sign SBL811R-K086/120-277VAC DIMENSIONS 8" H x 11" W x 2.5" D (est. 3.525 lbs) Class: SBL Series Control Method: Switch (not included) or external relay. CONSTRUCTION DANGER Back Construction: 0.050" Lift-n-Shift Back Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep. Face Material: 1/8" thick, dark grey diffused acrylic Faces: Single Faced Sign Finish: Duranodic Bronze Graphic: Printed graphic applied to surface 5 **ELECTRICAL** 8 in Flashing: Not Included Input Voltage: 120-277 VAC UL/cUL Listed: Listed Color: Black opaque Font: Swiss 721 Bold BT Illumination: Backlit with LEDs. Message blanks out when off. Sign Messages: See message table below laterin _____ ≥ 1/2 in _____ > -11 in MESSAGE LED/COLOR | HEIGHT | AMPS DANGER LASER EN COURS LASER IN USE w/Caution Symbols Red Wide Angle LED 2.0", 1.75", 0.75" 0.039-0.017 Frame Detail NOTE: Above messages are independently controlled. **Directional Systems** 2201 W 50th Št. **Directional** Systems Erie. PA 16509

Phone: (877) 827-8296 Fax: (877) 827-8291 Email: sales@directionalsystems.com Website: www.directionalsystems.com

MODEL

CLASS

MESSAGE