

PRODUCT ID: 39595

Outdoor Blank-out LED Backlit Sign

MODEL  
PHX1434AG-K162/120-277VAC



DIMENSIONS  
14" H x 34" W x 2.5" D (est. 11.285 lbs)

CLASS  
Class: PHX Series  
Control Method: Switch (not included) or external relay.

CONSTRUCTION  
Back Construction: 0.050" Lift-n-Shift Back  
Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep.  
Face Material: 1/8" thick, dark grey diffused acrylic  
Faces: Single Faced Sign  
Finish: Duranodic Bronze  
Graphic: Printed graphic applied to surface  
Mounting Channel: None

ELECTRICAL  
Flashing: Not Included  
Input Voltage: 120-277 VAC  
UL/cUL Listed: Listed for wet locations

MESSAGE  
Color: Black opaque  
Font: Swiss 721 Bold BT  
Illumination: Backlit with high intensity LEDs. Message blanks out when off  
Sign Messages: See message table below

MESSAGE	LED/COLOR	HEIGHT	AMPS
DRIVE THRU w/Left Arrow	Amber, Green Wide Angle LED	9.0", 3.75"	0.693-0.300

NOTE: Above messages are independently controlled.

Directional Systems  
2201 W 50th St.  
Erie, PA 16509  
Phone: (877) 827-8296  
Fax: (877) 827-8291  
Email: sales@directionalsystems.com  
Website: www.directionalsystems.com



Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



Frame Detail

