Outdoor Blank-out LED Direct-view Sign TCL1440G-L288/120-277VAC DIMENSIONS 14" H x 40" W x 2.5" D (est. 14.045 lbs) CLASS: TCL Series Control Method: Switch (not included) or external relay. CONSTRUCTION Back Construction: 0.050" Lift-n-Shift Back Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep. Face Material: 1/8" impact resistant, smoke-tinted acrylic (5109) Faces: Single Faced Sign Finish: Duranodic Bronze Mounting Channel: None **ELECTRICAL** Flashing: Not Included Input Voltage: 120-277 VAC Photodimming: None UL/cUL Listed: Listed for wet locations MESSAGE Illumination: Super bright direct view LEDs. Message blanks out when off. Sign Messages: See message table below MESSAGE LED/COLOR |HEIGHT|AMPS EXIT w/ Left Arrow Green Wide Angle LED 9.0" 0.411-0.178 40" Frame Detail NOTE: Above messages are independently controlled. **Directional Systems** 2201 W 50th Št. **Directional** Systems Erie. PA 16509 Phone: (877) 827-8296 Fax: (877) 827-8291 Email: sales@directionalsystems.com Website: www.directionalsystems.com

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.

14"

<u>⊢ 2.5"</u> −

Product View

Copyright (C) 2025 Directional Systems

PRODUCT ID: 43207

MODEL

CLASS