PRODUCT ID: 49084

Outdoor Blank-out LED Direct-view Sign

MODEL

TCL734R-125/12-24VDC



DIMENSIONS

7" H x 34" W x 2.5" D (est. 6.646 lbs)

CLASS

CLASS: TCL Series

Control Method: Switch (not included) or external relay.

CONSTRUCTION

Back Construction: 0.050" Lift-n-Shift Back

Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep. Face Material: 1/8" impact resistant, smoke-tinted acrylic (5109)

Faces: Single Faced Sign Finish: Duranodic Bronze Mounting Channel: None

ELECTRICAL

Flashing: Not Included Input Voltage: 12-24 VDC Photodimming: None
UL/cUL Listed: Listed for wet locations

MESSAGE

Illumination: Super bright direct view LEDs. Message blanks out when off.

Sign Messages: See message table below

MESSAGE		LED/COLOR	HEIGHT	AMPS
	ATM	Red Wide Angle LED	4.0"	0.307-0.153

NOTE: Above messages are independently controlled.

Directional Systems


2201 W 50th St. Erie. PA 16509 Phone: (877) 827-8296



Fax: (877) 827-8291 Email: sales@directionalsystems.com Website: www.directionalsystems.com

Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



Frame Detail

