PRODUCT ID: 49287

Outdoor Blank-out LED Direct-view Sign

MODEL

TCL1010DRGRG-175TS/12-24VDC



DIMENSIONS

10" H x 10" W x 5.5" D (est. 5.951 lbs)

CLASS

CLASS: TCL Series

Control Method: Switch (not included) or external relay.

CONSTRUCTION

Back Construction: 0.050" Lift-n-Shift Back

Cabinet: Corrosion resistant, extruded aluminum frame. 5.5" deep, mitered

Face Material: 1/8" impact resistant, smoke-tinted acrylic (5109)
Faces: Double Faced Sign
Finish: Duranodic Bronze
Mounting Channel: None

ELECTRICAL

Flashing: Not Included Input Voltage: 12-24 VDC Photodimming: None
UL/cUL Listed: Listed for wet locations

MESSAGE

Illumination: Super bright direct view LEDs. Message blanks out when off. Sign Messages: See message table below

MESSAGE	LED/COLOR	HEIGHT	AMPS
X	Red Wide Angle LED	8.375"	0.480-0.240
Down Arrow	Green Wide Angle LED	8.125"	0.747-0.373
X	Red Wide Angle LED	8.375"	0.480-0.240
Down Arrow	Green Wide Angle LED	8.125"	0.747-0.373

NOTE: Above messages are independently controlled.

Directional Systems

2201 W 50th St. Erie. PA 16509

Directional Systems Phone: (877) 827-8296 Fax: (877) 827-8291


Email: sales@directionalsystems.com Website: www.directionalsystems.com

Product View


NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.

Side A

10 in



Side B



Sample Display Options







-5 1/2 in -



