# PRODUCT ID: 5079

Outdoor Blank-out LED Direct-view Sign

#### MODEL

TCL1418G-121/120-277VAC



#### DIMENSIONS

14" H x 18" W x 2.5" D (est. 8.152 lbs)

# **CLASS**

CLASS: TCL Series

Control Method: Switch (not included) or external relay.

# **CONSTRUCTION**

Back Construction: 0.050" Lift-n-Shift Back

Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep. Face Material: 1/8" impact resistant, smoke-tinted acrylic (5109)

Faces: Single Faced Sign Finish: Duranodic Bronze Mounting Channel: None

### **ELECTRICAL**

Flashing: Not Included Input Voltage: 120-277 VAC Photodimming: None
UL/cUL Listed: Listed for wet locations

### **MESSAGE**

Illumination: Super bright direct view LEDs. Message blanks out when off.

Sign Messages: See message table below

MESSAGE	LED/COLOR	HEIGHT	AMPS
ATM I AND	Groon Wide Angle LED	3 75"	0 117 0 051

A I M LANE | Green Wide Angle LED | 3.75" | 0.11/-0.051

NOTE: Above messages are independently controlled.

# **Directional Systems**


2201 W 50th St. Erie. PA 16509 Phone: (877) 827-8296



Fax: (877) 827-8291 Email: sales@directionalsystems.com Website: www.directionalsystems.com

# **Product View**

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.







06192020 | DP