# **PRODUCT ID: 51899**

Outdoor Blank-out LED Backlit Sign

#### MODEL

PHX734G-165/12-24VDC



#### DIMENSIONS

7" H x 34" W x 2.25" D (est. 7.151 lbs)

## **CLASS**

Class: PHX Series

Control Method: Switch (not included) or external relay.

## CONSTRUCTION

Cabinet: 1-piece, corrosion resistant, extruded all-weather frame, 2.25" deep.

Face Material: 1/8" thick, dark grey diffused acrylic

Faces: Single Faced Sign Finish: Duranodic Bronze Mounting Channel: None

#### **ELECTRICAL**

Flashing: Not Included Input Voltage: 12-24 VDC

UL/cUL Listed: Listed for wet locations

## **MESSAGE**

Color: Black opaque Font: Swiss 721 Bold BT

Illumination: Backlit with high intensity LEDs. Message blanks out when off

Sign Messages: See message table below

MESSAGE	LED/COLOR	HEIGHT	<b>AMPS</b>

24 HR ATM Green Wide Angle LED | 3.75" | 3.467-1.733

NOTE: Above messages are independently controlled.

# **Directional Systems**

2201 W 50th St. Erie. PA 16506 Phone: (877) 827-8296


**Directional** Systems

Fax: (877) 827-8291 Email: sales@directionalsystems.com Website: www.directionalsystems.com Proudly Made in the USA

# **Product View**

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.





Frame Detail

