PRODUCT ID: 51940

Outdoor Blank-out LED Backlit Sign

MODEL

PHX718G-180/12-24VDC



DIMENSIONS

7" H x 18" W x 2.5" D (est. 4.304 lbs)

CLASS

Class: PHX Series

Control Method: Switch (not included) or external relay.

CONSTRUCTION

Back Construction: 0.050" Lift-n-Shift Back

Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep.

Face Material: 1/8" thick, dark grey diffused acrylic

Faces: Single Faced Sign Finish: Duranodic Bronze

Graphic: Printed graphic applied to surface Mounting Channel: None

ELECTRICAL

Flashing: Not Included Input Voltage: 12-24 VDC
UL/cUL Listed: Listed for wet locations

MESSAGE

Color: Black opaque Font: Swiss 721 Bold BT

Illumination: Backlit with high intensity LEDs. Message blanks out when off

Sign Messages: See message table below

MESSAGE LED/COLOR | HEIGHT | AMPS

OPEN Green Wide Angle LED | 3.75" | 1.947-0.973

NOTE: Above messages are independently controlled.

Directional Systems

2201 W 50th St. Erie. PA 16509 Phone: (877) 827-8296

Fax: (877) 827-8291



Email: sales@directionalsystems.com Website: www.directionalsystems.com

Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.





