PRODUCT ID: 5344

Outdoor Blank-out LED Direct-view Sign

MODEL TCL1442AGRAGR-300/120-277VAC



DIMENSIONS 14" H x 42" W x 2.5" D (est. 16.619 lbs)

CLASS

CLASS: TCL Series Control Method: Switch (not included) or external relay.

CONSTRUCTION

Back Construction: 0.050" Lift-n-Shift Back Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep. Face Material: 1/8" impact resistant, smoke-tinted acrylic (5109) Faces: Single Faced Sign Finish: Duranodic Bronze Mounting Channel: None

ELECTRICAL

Flashing: Not Included Input Voltage: 120-277 VAC Photodimming: None UL/cUL Listed: Listed for wet locations

MESSAGE

Illumination: Super bright direct view LEDs. Message blanks out when off. Sign Messages: See message table below

MESSAGE	LED/COLOR	HEIGHT	AMPS
ATMAmber Wide Angle LED3.5"0.027-0.012TELLERAmber Wide Angle LED3.5"0.040-0.017OPENGreen Wide Angle LED3.5"0.053-0.023CLOSEDRed Wide Angle LED3.5"0.040-0.017OPENGreen Wide Angle LED3.5"0.040-0.017OPENGreen Wide Angle LED3.5"0.040-0.017OPENGreen Wide Angle LED3.5"0.040-0.017OPENGreen Wide Angle LED3.5"0.040-0.017OPENRed Wide Angle LED3.5"0.040-0.017NOTE: Above messages are independently controlled.0.040-0.017			
Directional Systems 2201 W 50th St. Erie, PA 16509 Phone: (877) 827-8296 Fax: (877) 827-8291 Email: sales@directionalsystems.com Website: www.directionalsystems.com			

Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



Sample Display Options



Copyright (C) 2025 Directional Systems