

PRODUCT ID: 5385  
Outdoor Blank-out LED Direct-view Sign

MODEL  
TCL1442GGRGGR-300/120-277VAC



DIMENSIONS  
14" H x 42" W x 2.5" D (est. 16.45 lbs)

CLASS  
CLASS: TCL Series  
Control Method: Switch (not included) or external relay.

CONSTRUCTION  
Back Construction: 0.050" Lift-n-Shift Back  
Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep.  
Face Material: 1/8" impact resistant, smoke-tinted acrylic (5109)  
Faces: Single Faced Sign  
Finish: Duranodic Bronze  
Mounting Channel: None

ELECTRICAL  
Flashing: Not Included  
Input Voltage: 120-277 VAC  
Photodimming: None  
UL/cUL Listed: Listed for wet locations

MESSAGE  
Illumination: Super bright direct view LEDs. Message blanks out when off.  
Sign Messages: See message table below

| MESSAGE | LED/COLOR            | HEIGHT | AMPS        |
|---------|----------------------|--------|-------------|
| ATM     | Green Wide Angle LED | 3.5"   | 0.039-0.017 |
| OPEN    | Green Wide Angle LED | 3.5"   | 0.055-0.024 |
| CLOSED  | Red Wide Angle LED   | 3.5"   | 0.041-0.018 |
| TELLER  | Green Wide Angle LED | 3.5"   | 0.065-0.028 |
| OPEN    | Green Wide Angle LED | 3.5"   | 0.055-0.024 |
| CLOSED  | Red Wide Angle LED   | 3.5"   | 0.041-0.018 |

NOTE: Above messages are independently controlled.

Directional Systems  
2201 W 50th St.  
Erie, PA 16509  
Phone: (877) 827-8296  
Fax: (877) 827-8291  
Email: sales@directionalsystems.com  
Website: www.directionalsystems.com



Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



Sample Display Options



Frame Detail

