

**PRODUCT ID: 54750**  
Outdoor Blank-out LED Backlit Sign

**MODEL**  
PHX1442G-K822/12-24VDC



**DIMENSIONS**  
14" H x 42" W x 2.5" D (est. 21.237 lbs)

**CLASS**  
Class: PHX Series  
Control Method: Switch (not included) or external relay.

**CONSTRUCTION**  
Back Construction: 0.050" Lift-n-Shift Back  
Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep.  
Face Material: 1/8" thick, dark grey diffused acrylic  
Faces: Single Faced Sign  
Finish: Duranodic Bronze  
Graphic: Printed graphic applied to surface  
Mounting Channel: None

**ELECTRICAL**  
Flashing: Not Included  
Input Voltage: 12-24 VDC  
UL/cUL Listed: Listed for wet locations

**MESSAGE**  
Color: Black opaque  
Font: Swiss 721 Bold BT  
Illumination: Backlit with high intensity LEDs. Message blanks out when off  
Sign Messages: See message table below

MESSAGE	LED/COLOR	HEIGHT	AMPS
24 HR ATM NIGHT DEPOSIT	Green Wide Angle LED	3.5"	8.240-4.120

NOTE: Above messages are independently controlled.

**Directional Systems**  
2201 W 50th St.  
Erie, PA 16509  
Phone: (877) 827-8296  
Fax: (877) 827-8291  
Email: sales@directionalsystems.com  
Website: [www.directionalsystems.com](http://www.directionalsystems.com)

**Directional**  
Systems

**Product View**

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



Frame Detail

