# PRODUCT ID: 54750

Outdoor Blank-out LED Backlit Sign

## MODEL

PHX1442G-K822/12-24VDC

## DIMENSIONS

14" H x 42" W x 2.5" D (est. 21.237 lbs)

## CLASS

**Class**: PHX Series
**Control Method**: Switch (not included) or external relay.

## CONSTRUCTION

**Back Construction**: 0.050" Lift-n-Shift Back
**Cabinet**: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep.
**Face Material**: 1/8" thick, dark grey diffused acrylic
**Faces**: Single Faced Sign
**Finish**: Duranodic Bronze
**Graphic**: Printed graphic applied to surface
**Mounting Channel**: None

## ELECTRICAL

**Flashing**: Not Included
**Input Voltage**: 12-24 VDC
**UL/cUL Listed**: Listed for wet locations

## MESSAGE

**Color**: Black opaque
**Font**: Swiss 721 Bold BT
**Illumination**: Backlit with high intensity LEDs. Message blanks out when off
**Sign Messages**: See message table below

| MESSAGE | LED/COLOR | HEIGHT | AMPS |
|---|---|---|---|
| 24 HR ATM NIGHT DEPOSIT | Green Wide Angle LED | 3.5" | 8.240-4.120 |

NOTE: Above messages are independently controlled.


**Directional Systems**
2201 W 50th St.
Erie, PA 16509
Phone: (877) 827-8296
Fax: (877) 827-8291
Email: sales@directionalsystems.com
**Website: www.directionalsystems.com**


# Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.

Frame Detail



Copyright (C) 2026 Directional Systems