PRODUCT ID: 55119

Indoor Blank-out LED Backlit Sign

MODEL

SBL1212R-N957/120-277VAC

DIMENSIONS

12" H x 12" W x 2.5" D (est. 4.694 lbs)

CLASS

Class: SBL Series
Control Method: Switch (not included) or external relay.

CONSTRUCTION

Back Construction: 0.050" Lift-n-Shift Back
Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep.
Face Material: 1/8" thick, dark grey diffused acrylic
Faces: Single Faced Sign
Finish: Duranodic Bronze
Graphic: Printed graphic applied to surface

ELECTRICAL

Flashing: Not Included
Input Voltage: 120-277 VAC
UL/cUL Listed: Listed

MESSAGE

Color: Black opaque
Font: Swiss 721 Bold BT
Illumination: Backlit with LEDs. Message blanks out when off.
Sign Messages: See message table below

MESSAGE	LED/COLOR	HEIGHT	AMPS
COVID-19 TESTING w/ Right Arrow	Red Wide Angle LED	1.75", 2.5"	0.065-0.028

NOTE: Above messages are independently controlled.

Directional Systems
2201 W 50th St.
Erie, PA 16509
Phone: (877) 827-8296
Fax: (877) 827-8291
Email: sales@directionalsystems.com
Website: www.directionalsystems.com

Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



Frame Detail



Copyright (C) 2026 Directional Systems