

**PRODUCT ID: 55283**  
Indoor LED Backlit Sign

**MODEL**  
SBLF718W-N9280/12-24VDC



**DIMENSIONS**  
7" H x 18" W x 2.5" D (est. 3.864 lbs)

**CLASS**  
Class: SBLF Series  
Control Method: Switch (not included) or external relay.

**CONSTRUCTION**  
Back Construction: 0.050" Lift-n-Shift Back  
Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep.  
Face Material: 1/8" thick, impact modified acrylic (0000)  
Faces: Single Faced Sign  
Finish: Duranodic Bronze  
Graphic: Printed graphic applied to surface

**ELECTRICAL**  
Flashing: Not Included  
Input Voltage: 12-24 VDC  
UL/cUL Listed: Listed

**MESSAGE**  
Color: Refer to message table (Orange Translucent)  
Font: Swiss 721 Bold BT  
Illumination: Backlit with white LEDs. Message always visible.  
Sign Messages: See message table below

MESSAGE	LED/COLOR	HEIGHT	AMPS
Mask Required Beyond This Point w/ Face Mask Symbol	White Wide Angle LED	1.625", 2.5"	0.880-0.440

NOTE: Above messages are independently controlled.

**Directional Systems**  
2201 W 50th St.  
Erie, PA 16509  
Phone: (877) 827-8296  
Fax: (877) 827-8291  
Email: sales@directionalsystems.com  
Website: www.directionalsystems.com



**Product View**

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



Frame Detail

