

PRODUCT ID: 6051

Outdoor Blank-out LED Direct-view Sign

MODEL

TCL734G-502/120-277VAC



DIMENSIONS

7" H x 34" W x 2.5" D (est. 7.795 lbs)

CLASS

CLASS: TCL Series

Control Method: Switch (not included) or external relay.

CONSTRUCTION

Back Construction: 0.050" Lift-n-Shift Back

Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep.

Face Material: 1/8" impact resistant, smoke-tinted polycarbonate (5109)

Faces: Single Faced Sign

Finish: Duranodic Bronze

Mounting Channel: None

ELECTRICAL

Flashing: Not Included

Input Voltage: 120-277 VAC

UL/cUL Listed: Listed for wet locations

MESSAGE

Illumination: Super bright direct view LEDs. Message blanks out when off.

Sign Messages: See message table below

MESSAGE	LED/COLOR	HEIGHT	AMPS
DEPOSITORY	Green Wide Angle LED	3.5"	0.115-0.050

NOTE: Above messages are independently controlled.

Directional Systems

2201 W 50th St.

Erie, PA 16509

Phone: (877) 827-8296

Fax: (877) 827-8291


Email: sales@directionalsystems.com

Website: www.directionalsystems.com

Directional
Systems

Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



Frame Detail

