Product View PRODUCT ID: 6281 NOTE: Sign image may not exactly represent the finished product. For illustration purposes only. Outdoor Blank-out LED Direct-view Sign MODEL TCL77A-224H/120-277VAC DIMENSIONS 7" H x 7" W x 2.5" D (est. 3.078 lbs) **CLASS** CLASS: TCL Series Control Method: Switch (not included) or external relay. CONSTRUCTION Back Construction: 0.050" Lift-n-Shift Back Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep. Face Material: Injection molded, impact resistant Lexan hood with Lexan lenses Faces: Single Faced Sign Finish: Duranodic Bronze Mounting Channel: None **ELECTRICAL** Flashing: Factory setting 55fpm. Input Voltage: 120-277 VAC Photodimming: None UL/cUL Listed: Listed for wet locations MESSAGE Illumination: Super bright direct view LEDs. Message blanks out when off. 7 in Sign Messages: See message table below LED/COLOR | HEIGHT | AMPS MESSAGE Amber Indicator Dot Amber Wide Angle LED 4.0" 0.033-0.014 Amber Indicator Dot (flashing) Amber Wide Angle LED 0.033-0.014 4.0" -2 1/2 in -- 5 1/2 in Frame Detail NOTE: Above messages are independently controlled. **Directional Systems** 2201 W 50th Št. **Directional** Systems Erie. PA 16509 Phone: (877) 827-8296 Fax: (877) 827-8291 Email: sales@directionalsystems.com Website: www.directionalsystems.com

Copyright (C) 2025 Directional Systems