PRODUCT ID: 6286

Outdoor Blank-out LED Direct-view Sign

MODEL TCL77G-224H/120-277VAC



DIMENSIONS 7" H x 7" W x 2.5" D (est. 3.383 lbs)

CLASS

CLASS: TCL Series Control Method: Switch (not included) or external relay.

CONSTRUCTION

Back Construction: 0.050" Lift-n-Shift Back Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep. Face Material: Injection molded, impact resistant Lexan hood with Lexan lenses Faces: Single Faced Sign Finish: Duranodic Bronze Mounting Channel: None

ELECTRICAL

Flashing: Factory setting 55fpm. Input Voltage: 120-277 VAC Photodimming: None UL/cUL Listed: Listed for wet locations

MESSAGE

Illumination: Super bright direct view LEDs. Message blanks out when off. Sign Messages: See message table below

MESSAGE	LED/COLOR	HEIGHT	AMPS
Green Indicator Dot	Green Wide Angle LED	4.0"	0.053-0.023
Green Indicator Dot (Flashing)	Green Wide Angle LED	4.0"	0.053-0.023


NOTE: Above messages are independently controlled.


Directional Systems 2201 W 50th St. Erie, PA 16509 Phone: (877) 827-8296 Fax: (877) 827-8291 Email: sales@directionalsystems.com Website: www.directionalsystems.com

Copyright (C) 2025 Directional Systems

Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.





Frame Detail

