

PRODUCT ID: 67979
DOT LED Blank-Out Sign

MODEL
 DOT3535RG-175/100-240VAC



DIMENSIONS
 35" H x 35" W x 6.5" D (est. 76.72 lbs)

CLASS
 Class: DOT Series
 Control Method: Switch (not included) or external relay.

CONSTRUCTION
 Cabinet: Extruded aluminum cabinet with welded seams, NEMA 4X rated/IP66.
 Hinged door with silicone gasket, tool-less stainless-steel latches. 6.5" Deep.
 Face Material: 1/8" impact resistant, smoke-tinted polycarbonate (5109)
 Faces: Single Faced Sign
 Finish: Powdercoat Black

ELECTRICAL
 Input Voltage: 100-240 VAC
 Photodimming: IR photocells for auto photodimming
 Power Supplies: No Redundancy
 UL/cUL Listed: Listed for wet locations

MESSAGE
 Illumination: Super bright direct view LEDs. Message blanks out when off.
 Sign Messages: See message table below

MESSAGE	LED/COLOR	HEIGHT	AMPS
X	Red Narrow Angle LED	26.0"	0.176-0.073
Down Arrow	Green Narrow Angle LED	26.0"	0.205-0.085


NOTE: Above messages are independently controlled.

Directional Systems
 2201 W 50th St.
 Erie, PA 16509
 Phone: (877) 827-8296
 Fax: (877) 827-8291
 Email: sales@directionalsystems.com
 Website: www.directionalsystems.com




Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



Sample Display Options



Frame Detail

